

GESTELL

AC STAHL



NCS s0502-b VR
Verkehrsweiß



VR Zinn



NCS S0500-N VR
Reinweiß



NCS S4000-N VR
Weißaluminium



CR Verchromt




NCS S7502-B VR
Anthrazitgrau



NCS S9000-N VR
Tiefschwarz




NCS S9000-N VR Matt
Tiefschwarz



NCS S3060-Y80R
Korallenrot



VR Rau Metallbronze




NCS S3060-Y
Currygelb




NCS S4050-B40G
Wasserblau



NCS S7020-G50Y
Olivgrün



NCS S8005-Y20R
Braun



NCS S6030-B
Capri Blau



Holzgetelle

LE

* geprägte
Ausführung



Faggio tinto miele /
Honey stained beech
wood / Hêtre teinté miel /
Buche Honig gefärbt /
Haya tenida miel



Faggio tinto castano /
Chestnut stained beech
wood / Hêtre teinté
châtaigne / Buche
Kastanie gefärbt /
Haya tenida castaño




Faggio tinto grigio
chiaro / Grey stained
beech wood / Hêtre
teinté gris / Buche
Grau gefärbt / Haya
tenida gris



Faggio tinto bruno /
dark brown stained
beech wood / Hêtre
teinté brun / Buche
Dunkel braun gefärbt /
Haya tenida pardo



Faggio tinto nero /
Black stained beech
wood / Hêtre teinté
noir / Buche
Schwarz gefärbt /
Haya tenida negro



Faggio tinto campione / Beech
wood, stained according to sample /
Hêtre teinté selon échantillon /
Kundenmuster gefärbt / Haya
tenida según muestra

Ordine minimo 10 pz / Minimum
order 10 pcs / Minimum de
commande 10 pièces /
Mindestbestell 10 Stück / Minimo
de compra 10 piezas

Stoffbezüge

TE

cat. **a**

fortis




35




33



47




38




16



34




54




56

cat. **a**

melva



70




72



02




83




87



09




20



39




06




94

cat. **b**


amsterdam




153



135



57



37




08



38




123




26

cat. **b**

inca



51



603



56




33



12



17



15



415




55




42



103



100




35




703

cat. **b**


medley
gabriel



67006




66010




61004



62054




68002




68005




61002




61003




61189




63064




63017




65011



64123




64019



63063

cat. **b**

mirage




411



573



625




569



643



426




572



236

cat. **e** 


chili
gabriel




68190




61174




62085




68195




60115



64199




64201



61175

cat. **e** 

convert



4467




4560




4511



4466




4313



4462




4056




4211

cat. **e**

fenice



103




551




505



52




351



601



451




454


cat. **e**  

in&out


Non utilizzabile per
Punto e To-Kyo/
Not suitable for
Punto and To-Kyo /
Pas disponible pour
Punto et To-Kyo /
Nicht benutzbar für
Punto und To-Kyo /
No utilizable para
Punto y To-Kyo.




K600




K700




K800




K400




K900




P600




P700




P800




P400



P900




U600



U700



U800




U400




U900

cat. **e** 


rondo
gabriel



61200



64226




68226




65220




68225



60144



67097



67112

cat. **e**


valencia



107-8032



107-1049



107-0035




107-9035




107-0020



107-2075




107-4003



107-4045



107-0034



107-0002




107-2062



107-2074



107-5001




107-3069

cat. **g**

mood
gabriel



1101




4104




5102




3102



1106



4106



4105




3104

cat. **g**




reviva


Non utilizzabile per
Punto e To-Kyo/
Not suitable
for Punto and
To-Kyo / Pas
disponible pour
Punto et To-Kyo /
Nicht benutzbar
für Punto und To-
Kyo / No utilizable
para Punto y
To-Kyo.




402



801




901




304




303



711



701




706

cat. l


fabthirty
rubelli




3019-5




3019-8




3019-9




3019-14




3019-15



3019-20




3019-23




3019-18

cat. l


remix 3
kvadrat




412




422




912




632




653




933



612




643




452




233




743




242



722



672




852


cat. **m**

ocean mastrotto

pelle / leather /
peau / leder / piel



418



433



435



414



413



437



428



429




446




405




422



439



440



443



421

Stoffe: Zusammensetzung und Test /

cat a fortis Composizione / Composition / Composition / Zusammensetzung / Composición: surface 100% PL; back 95% PL, 5% CO Peso / Weight / Poids / Gewicht / Peso: 305 g/m² ± 5% Prove / Tests / Tests / Test / Pruebas: Abrasion resistance EN ISO 12947-1,2: > 100.000 rubs; Pilling EN ISO 12945-2:2002: 5; Colour fastness to light ISO 105-B02: 5; Colour fastness to rubbing ISO 105-X12:2001: 4-5 dry – 5 wet; Fire resistance: BS 5852 part 1 Ignition source 0; Tensile strength ISO 13934-1: 1153 N (31,6%) warp – 739 N (26,9%) weft; Tear growth resistance ISO 13937-3: 127,6 N warp – 114,1 N weft; Resistance to seam slippage EN ISO 13936-2: 4,00 mm warp – 4,0 mm weft. Note / Notes / Remarques / Hinweise / Notas: water repellent	cat b amsterdam Composizione / Composition / Composition / Zusammensetzung / Composición: 100% PL Peso / Weight / Poids / Gewicht / Peso: 430 g/m² ± 5% Prove / Tests / Tests / Test / Pruebas: Abrasion resistance EN ISO 12947-1,2: > 100.000 rubs; Colour fastness to light ISO 105-B02: 5; Colour fastness to rubbing ISO 105-X12:2001: 5 dry – 4-5 wet; Tensile strength ISO 13934-1: 733 N (98,4%) warp – 791 N (131%) weft; Tear growth resistance ISO 13937-3: 80,8 N warp – 60,5 N weft; Resistance to seam slippage EN ISO 13936-2: 2,3 mm warp – 2,5 mm weft Note / Notes / Remarques / Hinweise / Notas: water repellent	Peso / Weight / Poids / Gewicht / Peso: 510 g/m Prove / Tests / Tests / Test / Pruebas: Abrasion resistance EN ISO 12947-1,2: 75.000 rubs; Pilling EN ISO 12945-2:2002: 4; Colour fastness to light ISO 105-B02: 5-7; Colour fastness to rubbing ISO 105-X12:2001: 4-5 dry – 4-5 wet; Fire resistance: BS EN 10211-2 cigarette and match; BS EN 1021-1 cigarette; BS 5852 part 1 0,1 cigarette & match; BS 476 Part 7, class 2; ÖNORM A3800-B2-B3825-Q1 UK; CA TB 117-2013; ASTM E 84 Class I Note / Notes / Remarques / Hinweise / Notas: US ACT: AAATCC 16 Light fastness, AATCC 8 or 116 Wet/dry crocking, ASTM D3511 Pilling, ASTM D4157-07 Wyz abrasion (heavy duty), CA TB 117-2013, ASTM E 84 Class I; Acoustic test air flow resistance EN 29053 & ISO 9053-1; Acoustic test sound absorption ISO 354 & ISO 11654; Sustainability: Standard 100 by OEKO-TEX	Note / Notes / Remarques / Hinweise / Notas: Sustainability: Standard 100 by OEKO-TEX; Acoustic test sound absorption ISO 354 cat e chili gabriel Composizione / Composition / Composition / Zusammensetzung / Composición: 100% PL (post-consumer recycled polyester fr) Peso / Weight / Poids / Gewicht / Peso: 470 g/ml Prove / Tests / Tests / Test / Pruebas: Abrasion resistance EN ISO 12947-1,2: 60.000 rubs; Pilling EN ISO 12945-2:2002: 4-5; Colour fastness to light ISO 105-B02: 5-8; Colour fastness to rubbing ISO 105-X12:2001: 4-5 dry – 4-5 wet; Fire resistance: Class 11M UNI 9175; BS EN 10211&2 cigarette and match; BS EN 1021-1 cigarette; BS 7176 Medium Hazard; BS 5852 Crib 5; BS 5852 Part 1 0,1 cigarette & match; CA TB 117-2013; NFP 92-503/504/505 M1; DIN 4102-B1; AM 18-NF D 60-013 (only for fabric); DIN EN 13501-1 B-s1, d0; Tensile strength ISO 13934-1
melva Composizione / Composition / Composition / Zusammensetzung / Composición: 100% PL Peso / Weight / Poids / Gewicht / Peso: 360 g/m² ± 5% Prove / Tests / Tests / Test / Pruebas: Abrasion resistance EN ISO 12947-1,2 : > 100.000 rubs; Pilling EN ISO 12945-2:2002 : 5; Colour fastness to light ISO 105-B02: 4; Colour fastness to rubbing ISO 105-X12:2001: 4-5; Fire resistance: EN 1021-1 cigarette; Tensile strength ISO 13934-1: 1077 N (36,9%) warp – 1708 N (35,9%) weft; Tear growth resistance ISO 13937-3 : 72,0 N warp – 179,1 N weft; Resistance to seam slippage EN ISO 13936-2: 3,3 mm warp – 3,5 mm weft	inca Composizione / Composition / Composition / Zusammensetzung / Composición: 88% PVC, 6% PL, 6% CO Peso / Weight / Poids / Gewicht / Peso: 650 g/m² Prove / Tests / Tests / Test / Pruebas: Abrasion resistance ISO 5470-2: > 100.000 rubs; Colour fastness to light ISO 105-B02: 7; Colour fastness to rubbing ISO 105-X12:2001: 4 dry – 4 wet; Fire resistance: 11M-UNI 9175; EN 1021 1/2; BS 5852 part 1; CA TB 117-2013; IMO FTP Code 307 pat 8; ÖNORM B 3825; Tensile strength ISO 1421, 300 N/5 cm warp – 200 N/5 cm weft Note / Notes / Remarques / Hinweise / Notas: phtalete free medley gabriel Composizione / Composition / Composition / Zusammensetzung / Composición: 100% PL	mirage Composizione / Composition / Composition / Zusammensetzung / Composición: 100% PL FR (Trevira Cs) Peso / Weight / Poids / Gewicht / Peso: 330 g/m² ± 10% Prove / Tests / Tests / Test / Pruebas: Abrasion resistance EN ISO 12947-1,2: 100.000 rubs +/-20%; Pilling EN ISO 12945-2:2002:4/5 ± ½; Colour fastness to light ISO 105-B02: 6 ± 1; Colour fastness to rubbing ISO 105-X12:2001: 4/5 ± ½; Fire resistance: Classe 11M; EN ISO 6940/6941; BS 5852 Crib 5 using a CM Foam 35 Kg/cu.m.; B1 DIN 4102; EN 1021 part 1-2 using a CM Foam 35 Kg/cu.m.; EN 13773 Class 1; EN 13501-1 esp 1,2; CA TB 117-2013; Fire Protection Classification 5.3; FAR.25853 Classification: yes; M1 + NF D 60-013:2006 AM18; B1-ÖNORM 3800 Part 1 + ÖNORM B3825; Azimut MED annex A.1 item:A.1/3.20 upholstered furniture	Note / Notes / Remarques / Hinweise / Notas: US ACT: AAATCC 16 Light fastness, AATCC 8 or 116 Wet/dry crocking, ASTM D3511 Pilling, ASTM D4157-07 Wyz abrasion (heavy duty) 100k, CA TB 117-2013; Sustainability: Standard 100 by OEKO-TEX; Acoustic test air flow resistance EN 29053 & ISO 9053-1 convert Composizione / Composition / Composition / Zusammensetzung / Composición: 100% PL (recycled polyester fr) Peso / Weight / Poids / Gewicht / Peso: 340 g/m² ± 10% Prove / Tests / Tests / Test / Pruebas: Abrasion resistance EN ISO 12947-1,2: 50.000 rubs ± 20%; Pilling EN ISO 12945-2:2002: 4/5

± ½; Colour fastness to light ISO 105-B02: 6 ± 1; Colour fastness to rubbing ISO 105-X12:2001: 4 ± 1; Fire resistance: Classe 11M; BS 5852 Crib 5 using a CM Foam 35 Kg/cu.m.; B1 DIN 4102; EN 1021 part 1-2 using a CM Foam 35 Kg/ cu.m.; CA TB 117-2013; M1 + NF D 60-013:2006 AM18; Azimut MED annex A.1 item:A.1/3.20 upholstered furniture

Note / Notes / Remarques / Hinweise / Notas:
Sustainability: OEKO TEX N.072150.O; Acoustic test sound absorption ISO 354

fenice

Composizione / Composition / Composition / Zusammensetzung / Composición:
75% WO, 25% PA

Peso / Weight / Poids / Gewicht / Peso:
335 g/m² ± 7%

Prove / Tests / Tests / Test / Pruebas:
Abrasion resistance EN ISO 12947-1,2: 100.000 rubs ± 20%; Pilling EN ISO 12945-2:2002: 4 ± 1; Colour fastness to light ISO 105-B02: 6 ± 1; Colour fastness to rubbing ISO 105-X12:2001: 4/5 ± ½; Fire resistance: Classe 11M using a standard FR polyurethane foam 25 kg/cu.m.; BS 5852 Crib 5 using a standard foam 20/22 kg/cu.m.; EN 1021 part 1-2 using a standard foam 20/22 kg/cu.m.; CA TB 117-2013

Note / Notes / Remarques / Hinweise / Notas:
Acoustic test sound absorption ISO 354; Acoustical charact. UNI EN ISO 10534-2

in&out

Composizione / Composition / Composition / Zusammensetzung / Composición:
100% PP

Peso / Weight / Poids / Gewicht / Peso:
k 595 g/m
p 550g/m
u 645 g/m

Prove / Tests / Tests / Test / Pruebas:
Abrasion resistance EN ISO 12947-1,2: 25.000 rubs; Pilling EN ISO 12945-2:2002: 4-5; Colour fastness to light ISO 105-B02: 7; Colour fastness to rubbing ISO 105-X12:2001: 4-5 dry – 4 wet; Resistance to seam slippage EN ISO 13936-2: 4 mm warp – 4 mm weft

Note / Notes / Remarques / Hinweise / Notas:
indoor&outdoor (no water repellent); UV resistant; Breathable; Antibacterical; Mold resistant; no-rot; Recyclable; Standard 100 by OEKO-TEX

rondo gabriel

Composizione / Composition / Composition / Zusammensetzung / Composición:
99% PL (post-consumer recycled polyester fr), 1% PL fr

Peso / Weight / Poids / Gewicht / Peso:
490 g/m

Prove / Tests / Tests / Test / Pruebas:
Abrasion resistance EN ISO 12947-1,2:70.000 rubs; Pilling EN ISO 12945-2:2002: 4-5; Colour fastness to light ISO 105-B02: 5-8; Colour fastness to rubbing ISO 105-X12:2001: 4-5 dry – 4-5 wet; Fire resistance: BS EN 1021-1 cigarette; BS EN 1021-2 match; CA TB 117-2013; Resistance to seam slippage EN ISO 13936-2: 3 mm warp - 3 mm weft

Note / Notes / Remarques / Hinweise / Notas: US ACT: AATCC 16 Light fastness, AATCC 8 or 116 Wet/dry crocking, ASTM D3511 Pilling, ASTM D4157-07 Wyz abrasion (heavy duty) 100k, CA TB 117-2013; Sustainability: STANDARD 100 by OEKO-TEX®; EU Ecolabel

valencia

Composizione / Composition / Composition / Zusammensetzung / Composición:
Vinyl / Urethane topcoat

Peso / Weight / Poids / Gewicht / Peso:
650 g/m²

Prove / Tests / Tests / Test / Pruebas:
Abrasion resistance EN ISO 12947-1,2 : 300.000 rubs; Fire resistance: UNI 9175 Classe 11M; EN 1021 Part 1 & 2; CAL TB 117-2013, Section E; UNE 23.727-90 1R/M.2; NF P 92-503/M2; DIN 4102 B2; ÖNORM B 3825, Gruppe 1 - Schwerbrennbares Verhalten; ÖNORM A 3800 Teil 1, Qualmbildungsklasse Q1 - schwachqualmend; IMO FTP 2010 Code MSC.307 (88) Part 8 3.1 & 3.2; FMVSS 302; FAR 25/853; MED (in its current valid version 2021); ECE R118.02 (replaces Directive 95/28/CE) Annexes 6, 7 & 8; EN 71-2:2006+A1:2007 - Safety of Toys - Parte 2: Flammability

Note / Notes / Remarques / Hinweise / Notas:
Antibacterial Protection; Antifungal Protection; Antimycotic Protection; PERMABLOK3®; Anti-stain Finish; Cold Crack -23°C; Mildew resistant backing and face; UV-Resistance XENOTEST DIN 54004/ NTC 1479; EN 71-3 Safety of Toys (Migration of certain elements); Sulfide Stain Resistant; Anti-static Finish

cat g

mood gabriel

Composizione / Composition / Composition / Zusammensetzung / Composición:
92% WO (New Zealand wool), 8% PA

Peso / Weight / Poids / Gewicht / Peso:
555 g/m

Prove / Tests / Tests / Test / Pruebas:
Abrasion resistance EN ISO 12947-1,2 : 100.000 rubs; Pilling EN ISO 12945-2:2002: 4; Colour fastness to light ISO 105-B02: 5-7; Colour fastness to rubbing ISO 105-X12:2001: 4-5 dry – 4-5 wet; Fire resistance: BS EN 1021-2 match; BS EN 1021-1 cigarette; BS 5852 part 1 Q,1 cigarette & match; BS 476 Part 7, class 1; Class Uno UNI 9175 Class 1 IM; CA TB 117-2013; Resistance to seam slippage EN ISO 13936-2: 1 mm warp - 2 mm weft

Note / Notes / Remarques / Hinweise / Notas:
US ACT: AATCC 16 Light fastness, AATCC 8 or 116 Wet/dry crocking, ASTM D3511 Pilling, ASTM D4966 Martindale (heavy duty), CA TB 117-2013; Sustainability: STANDARD 100 by OEKO-TEX®; EU Ecolabel

reviva

Composizione / Composition / Composition / Zusammensetzung / Composición:
100% recycled and recyclable PET (polyester yarn made by post-consumer plastic bottles)

Peso / Weight / Poids / Gewicht / Peso:
585 g/m

Prove / Tests / Tests / Test / Pruebas:
Abrasion resistance EN ISO 12947-1,2 : 50.000 rubs; Pilling EN ISO 12945-2:2002: 4; Colour fastness to light ISO 105-B02: 7; Colour fastness to rubbing ISO 105-X12:2001: 4-5 dry – 4 wet; Fire resistance: Classe 11M UNI 9175; EN 1021-1+2; BS 5852:2006 cigarette + flame; CA TB 117-2013; M1 Francia (NF P92); Resistance to seam slippage EN ISO 13936-2: 4 mm warp - 4 mm weft

Note / Notes / Remarques / Hinweise / Notas:
indoor&outdoor (no water repellent)

cat l

fabthirty rubelli

Composizione / Composition / Composition / Zusammensetzung / Composición:
100% PL

Peso / Weight / Poids / Gewicht / Peso:
670 gr

Prove / Tests / Tests / Test / Pruebas:
Abrasion resistance EN ISO 12947-1,2 : 50.000 rubs; Pilling EN ISO 12945-2:2002:4; Colour fastness to light ISO 105-B02: 7; Colour fastness to rubbing ISO 105-X12:2001: 4-5 dry – 4-5 wet; Fire resistance: BS 5852 part 0,1 cigarette + match; BS 7176 contract upholstery; CA TB 117-2013; M1 NFP902-503-504-505; B1 DIN 4102-1; IMO 8 Upholstery

Note / Notes / Remarques / Hinweise / Notas:
Sustainability: Greenguard Gold, STANDARD 100 by OEKO-TEX®

remix 3 kvadrat

Composizione / Composition / Composition / Zusammensetzung / Composición:
90% WO (new wool) + 10% NY

Peso / Weight / Poids / Gewicht / Peso:
420 g/m

Prove / Tests / Tests / Test / Pruebas:
Abrasion resistance EN ISO 12947-1,2: 100.000 rubs; Pilling EN ISO 12945-2:2002: 4; Colour fastness to light ISO 105-B02: 6-7; Colour fastness to rubbing ISO 105-X12:2001: 4-5 dry – 4-5 wet; Fire resistance: UNI 9175 11M; EN 1021-1/2; BS 5852 ignition source 3; BS 5852 part 1; CA TB 117-2013; IMO FTP Code 2010: part 8; NF D60 013; NFPA 260; AS/NZS 1530.3; AS/NZS 3837 class 2; ÖNORM B1/Q1; Resistance to seam slippage EN ISO 13936-2: 5 mm warp - 3 mm weft

Note / Notes / Remarques / Hinweise / Notas:
Acoustic test air flow resistance EN 29053; Acoustic test sound absorption ISO 354; Complies with Möbelfakta; Sustainability: EU Ecolabel, Greenguard Gold, HPD, EPD

cat m

ocean mastrotto

Composizione / Composition / Composition / Zusammensetzung / Composición:
leather

Prove / Tests / Tests / Test / Pruebas:
Colour fastness to light ISO 105-B02: 5; Colour fastness to rubbing UNI EN ISO 11640:1998 : 4; Fire resistance: BS 5852:1979; BS EN 1021-1-2:2006; Tear strength UNI EN ISO 3377-1: 20N